

Stauna Coat Instructions

Oceanic Stauna Coat is provided with all Traditional and Infra-red Stauna cabins for the purpose of protecting the timber from condensing steam from the mini steam generator.

Application

- To apply the liquid use a paint brush, do not use a roller as this will absorb too much liquid.
- 1ltr of the substance will cover approximately 15sqm of timber.
- All internal timber surfaces of the sauna cabin should be coated in the liquid.
- We recommend two applications once before assembly and once after.

Application of any other type of varnish or treatment to the timber is not recommended as they may release toxins into the atmosphere during use of the sauna. Stauna Coat has been specially selected for its lack of toxicity and is safe to be used in a sauna environment.

Safety Precautions

The coating is not considered hazardous (in accordance with OSHA Haz Com 2012, 29 CFR 1910.1200 and Regulation (EC) No1272/2008(CLP)) but the following safety procedures should be taken:

- Following contact with eyes : Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
- Following contact with skin : Wash with soap and water. Remove and launder contaminated clothing. Get medical attention if irritation develops or persists.
- Following ingestion : Seek immediate medical attention. Do not induce vomiting.
- Following inhalation : Remove to fresh air. If not breathing, give artificial respiration by trained personnel. Consult a physician.